




CS-HZ35ZKE + CU-HZ35ZKE



Panasonic HZ25ZKE Flaggskepp Inverter+ - R32		
		4.20 kW
Maximum capacity	kW	7,90kW
Reference		CS-HZ35ZKE + CU-HZ35ZKE
Heating capacity (Nominal)	kW	4,20
Heating capacity (Min)	kW	0,85
Heating capacity (Max)	kW	7,90
COP (1)	W/W	5,00
Heating capacity at -7°C (2)	kW	5,12
COP at -7°C (1)	W/W	2,56
Heating capacity at -15°C (2)	kW	5,00
COP at -15°C (1)	W/W	2,53
Heating capacity at -20°C (2)	kW	4,30
COP at -20°C (1)	W/W	2,36
Heating capacity at -25°C (2)	kW	3,70
COP at -25°C (1)	W/W	2,20
SCOP (3)		5,30 A+++
Pdesign at -10°C	kW	4,00
Input power heating (Nominal)	kW	0,84
Input power heating (Min)	kW	0,17
Input power heating (Max)	kW	2,25
Annual energy consumption heating (4)	kWh/a	1.057
Cooling capacity (Nominal)	kW	3,50
Cooling capacity (Min)	kW	0,85
Cooling capacity (Max)	kW	4,60
SEER (3)		8,60 A+++
Pdesign (cooling)	kW	3,50
Input power cooling (Nominal)	kW	0,80
Input power cooling (Min)	kW	0,17
Input power cooling (Max)	kW	1,20
Annual energy consumption cooling (4)	kWh/a	142
Indoor unit		CS-HZ35ZKE
Indoor power source	V	230
Indoor air flow (Heat)	m³/min	15,7
Indoor air flow (Cool)	m³/min	14,1
Moisture removal volume	L/h	2,0
Indoor sound pressure (Heat -Hi) (5)	dB(A)	45
Indoor sound pressure (Heat -Lo) (5)	dB(A)	25

Panasonic HZ25ZKE Flaggskepp Inverter+ - R32		
		4.20 kW
Indoor sound pressure (Heat -Q-Lo) (5)	dB(A)	18
Indoor sound pressure (Cool -Hi) (5)	dB(A)	44
Indoor sound pressure (Cool -Lo) (5)	dB(A)	28
Indoor sound pressure (Cool -Q-Lo) (5)	dB(A)	19
Indoor dimension (Height)	mm	295
Indoor dimension (Width)	mm	870
Indoor dimension (Depth)	mm	229
Indoor net weight	kg	11
nanoe X Generator		Mark 3
Outdoor unit		CU-HZ35ZKE
Outdoor air flow (Heat)	m³/min	34,4
Outdoor air flow (Cool)	m³/min	34,4
Outdoor sound pressure (Heat -Hi) (5)	dB(A)	50
Outdoor sound pressure (Heat -Lo) (5)	dB(A)	47
Outdoor sound pressure (Cool -Hi) (5)	dB(A)	48
Outdoor sound pressure (Cool -Lo) (5)	dB(A)	45
Outdoor dimension (Height) (6)	mm	622
Outdoor dimension (Width) (6)	mm	824
Outdoor dimension (Depth) (6)	mm	299
Outdoor net weight	kg	34
Pipe diameter (Liquid)	Inch (mm)	1/4 (6,35)
Pipe diameter (Gas)	Inch (mm)	3/8 (9,52)
Pipe length range	m	3 ~ 20
Elevation difference (in/out) (7)	m	10
Pipe length for additional gas	m	7,5
Additional gas amount	g/m	10
Refrigerant (R32) / CO2 Eq.	kg / T	0,90 / 0,61
Operating range (Heat - Min)	°C	-25
Operating range (Heat - Max)	°C	+24
Operating range (Cool - Min)	°C	+16
Operating range (Cool - Max)	°C	+43

Kompletterande produkter



CZ-CAPRA1 RAC interface
adapter for integration
into P Link



CZ-RD517C. Wired remote
controller for wall-mounted
and floor console