

ATTIVA XTR 4.6



48 VOLT WITH AC SYSTEM

6 X 8V LEAD-ACID BATTERIES

22x11-12 ALUMINUM RIMS

FRONT & REAR LED LIGHTS

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com









ATTIVA XTR 4.6



places:	4
batteries:	6 x 8V, US8VGC standard
motor:	AC 48V - Mahle Letrika
controller:	sevcon GEN4 - AC - 450A
transmission:	rear axle, 19 spline, ratio 16:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	20% (then 11°)
vehicle dimensions:	
overall	3000mm x 1400mm x 2150mm
ground clearance (empty):	350mm
turning radius (min):	3,5 mt
wheel base	1710mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel
front	disc
rear	disc
tyres: recommended pressure:	22x11-12 with aluminum rims 2 bar (29psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear LED lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

seguici su - follow us on





clicca mi piace - like us on





all above specification were correct at the time of the publishing and are indicatives and not binding. ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice